MALU.U.D. UUTI Form 9-331 (May 1963) U. FED STATES SUBMIT IN TRI CATE* Form approved. DEPARTMENT OF THE INTERIOR (Other Instruction verse side) Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO. NM-0384576 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME GAS WELL WELL X OTHER 2. NAME OF OPERATOR 8. FARM OR LEASE NAME General Operating Company Stevens-Federal 3. ADDRESS OF OPERATOR 8. WELL NO. ARTEMA, OFFICE Suite 1007 Ridglea Bank Building, Ft. Worth, Texas 76116 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT At surface Grayburg Jackson Q-SA 1650' FNL and 1980' FEL Section 35-T17S-R30E N.M.P.M. 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 35-T17S-R30E N.M.P.M. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 14. PERMIT NA ISSUED: 12. COUNTY OR PARISH | 13. STATE 3535' GR, 3544' RKB 5/22/74 New Mexico 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING ABANDONMENT* Running Surface Casing REPAIR WELL CHANGE PLANS (Other) __ (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) * General Operating Company's Stevens Federal Well No.1 was spudded on May 23, 1974 with WEK Drilling Company rotary tools. 14-3/4-inch surface hole was drilled to 505' RKB, and 10-3/4" OD, 40.5# surface casing was set at 501' RKB and cemented with 100 sacks Class C cement with 2% CaCl on May 24, 1974. Cement was allowed to set 12 hours before pressure testing surface casing to 600 psig and commencing drilling of 7-7/8" hole below surface casing. ACCEPTED FOR RECORD U.S. GEOLOGICAL SURVEY ROSWELL, NEW MENICO 18. I hereby certify that the foregoing is true and correct