

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult your Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments. **Items 22 and 24:** If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequate for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing intervals. **Item 33:** Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			38.	GEOLOGIC MARKERS	
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOI MEAS. DEPTH
Metex	2400'	2446'		Queen	1856
Grayburg	2800'	3018'		San Andres	2558
San Andres	3168'	3369'		Lovington Sand	2652
Fraced	3350'	3369'	With 20,000# sand and 20,000 gallons water.		
Fraced	3168'	3176'	With 20,000# sand and 20,000 gallons water.		
Fraced	2970'	3018'	With 30,000# sand and 30,000 gallons water.		
Acidized	2800'	2862'	With 6,500 gallons acid.		
Fraced	2400'	2446'	With 30,000#sand and 30,000 gallons water.		



KENNETH D. REYNOLDS - ARTESIA
LESLIE K. EVERTSON - ROSWELL

DRILLING CO., INC. - OIL WELL DRILLING CONTRACTORS

P. O. Box 2055 ROSWELL, NEW MEXICO 88201
TELEPHONES: ARTESIA 746-6757
ROSWELL 623-5070

11/5/74

General American Oil Co. of Texas
Box 416
Loco Hills, N. M. 88255

Re: Burch B #28

Gentlemen:

The following is a Deviation Survey of the above well:

420' - $\frac{1}{4}$
920' - $\frac{1}{2}$
1410' - $\frac{1}{2}$
1785' - 1
2249' - 1
2669' - 1
3100' - 1
3420' - 1

Yours very truly,

WEK DRILLING CO., INC.

Kenneth D. Reynolds

STATE OF NEW MEXICO)
COUNTY OF CHAVES)

The foregoing was acknowledged before me this 5th
day of November, 1974, by Kenneth D. Reynolds.

Notary Public

My Commission Expires:
