

Form 9-331  
(May 1963)

1-R.J.Starrak-Tulsa 1-BDH-Hobbs

1-E.F.-Doremann N. M. O. C. C. COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TR (Other instruct  
verse side)CATE\*  
on re-Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-029418-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

RECEIVED

2. NAME OF OPERATOR

Getty Oil Company

JUL 27 1978

3. ADDRESS OF OPERATOR

P.O. Box 730 Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surfaceO.C.C.  
ARTESIA, OFFICE

Unit Letter O, 510' FSL &amp; 1980' FEL

7. UNIT AGREEMENT NAME

Skelly Unit

8. FARM OR LEASE NAME

Skelly Unit

9. WELL NO.

139

10. FIELD AND POOL, OR WILDCAT

Fren 7-Rivers

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 23, T-17-S, R-31-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3861 GR

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

18.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

LaRue spudded 11" hole at 8:00 A.M. on 5-30-78. Drilled 11" hole to 700'  
Set 8 5/8" 24# 8rd casing at 699', and B.J. cemented with 150 sxs 50/50  
Poz, 4% Gel, 1/4# Cello Flakes/sx; 125 sxs Class "C" w/2% CaCL. Total cement  
275 sxs. 40 sacks cement circulated. Tested casing with 1000# for 30  
minutes with no drop in pressure.

RECEIVED

JUL 21 1978  
U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

19. I hereby certify that the foregoing is true and correct

SIGNED

(Signed) D. R. CROCKETT

TITLE

Area Superintendent

DATE

7-20-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACTING DISTRICT ENGINEER

DATE

JUL 26 1978

\*See Instructions on Reverse Side