

N.M.O.C.D. COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 028936 (d)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

JUL 10 1980

8. FARM OR LEASE NAME

Federal L O. C. D.

9. WELL NO.

ARTESIA, OFFICE

7

10. FIELD AND POOL, OR WILDCAT

Loco Hills-Queen  
Grayburg-San Andres11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

31 - 17S - 30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a well. Use "APPLICATION FOR PERMIT" for such proposals.

JUL - 8 1980

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

1. NAME OF OPERATOR

Anadarko Production Company

2. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface

660' FNL & 660' FWL Sec. 31, T17S, R30E  
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3582' GL

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

## SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other)

Grayburg Completion

XX

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rigged up pulling unit; rigged up Dresser-Atlas.
2. Perforated Grayburg Zone - Select Fire @ 1 shot each @ 2791,92,93; 2857,58,59,65,66, 80,81,82; 2948,49,50,66,67,68 - total 17 holes w/.31" diam.
3. Straddled perfs: 2791-93, acidized w/3 bbls 15% NE acid, overflushed with 10 BFW.  
2857-82, acidized w/5 bbls 15% NE acid + 12 BS, overflushed with 10 BFW.  
2948-68, acidized w/4 bbls 15% NE acid + 9 BS, overflushed with 10 BFW.
4. Set Bridge Plug @ 3080'; spotted 30' sand on top of BP.
5. Dowell fraced Grayburg perforations down 4 1/2" casing (Limited Entry) with a total of: 1500 gals 15% NE acid, 40,000 gals Redifrac 40, 20,000# FLA-100, 10,000# 10/20 sand & 26,000# 20/40 sand. AR&P = 30 BPM @ 2500#.
6. Washed sand off BP; TOH with BP.
7. Ran tubing with SNOE @ 3266'; ran bottom-hole pump & rods. Returned well to production.

18. I hereby certify that the foregoing is true and correct

SIGNED

*[Signature]*

TITLE

Area Supervisor

DATE

July 7, 1980

(This space for Federal or State office use)

APPROVED BY

*[Signature]*

TITLE

DATE

1980

CONDITIONS OF APPROVAL, IF ANY: