

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Anadarko Production Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 67, Loco Hills, New Mexico 88255

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FN&ELs Sec. 34, T17S, R30E

AT TOP PROD. INTERVAL: **Same**

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other) _____	

SUBSEQUENT REPORT OF

U

OIL & GAS
U.S. GEOLOGICAL SURVEY
BOSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

☒ Spud, set & cement surface, int & pdn csg.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up rotary tools; spudded 17½" hole @ 7:30 AM 12-15-81 & drilled to 420'.
 2. Ran 10 jts 13-3/8", 48#, H-40 ST&C csg with csg shoe @ 418'. Halliburton cemented with 400 sx Class H with 2% CaCL; circulated 60 sx to pit. PD @ 6:45 PM 12-15-81. Installed 12" Shaffer Type B Hydraulic BOP & tested to 650 psi.
 3. WOC total of 24 hours prior to drilling plug on 13-3/8" csg with 12½" bit. Drilled to 3610' (temporarily lost circulation @ 953').
 4. Ran 36 jts (1544') 8-5/8", 28# S-80, ST&C, 8rd Cond. A csg +
3 jts (118') 8-5/8", 24# K-55, ST&C, 8rd Cond. A csg +
40 jts (1809') 8-5/8", 24# J-55, ST&C, 8rd Cond. A csg with csg shoe @ 3464'. Halliburton cemented with 2500 sx Hal. Lite w/12# Salt/sx, 10# Gilson-ite/sx, ½# Flocele/sx (mix 12.7#/gal) and tailed-in with 300 sx Class H w/2% CaCL (mix 15.6#/gal). PD @ 5:20 AM 12-27-81; circulated 185 sx to pit.
 5. Installed 12" Shaffer Type B Hydraulic BOP & tested to 1000 psi.
- continued on Page 2

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

~~RECEIVED FOR RECORD~~
~~ROGER A CHAPMAN~~

TITLE Area Supervisor DATE February 25, 1982

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL ANY:

U.S. GEOLOGICAL SURVEY
POSWELL, NEW MEXICO

***See Instructions on Reverse Side**