(Other .ructions on reverse side) UNITED STATES

DEPARTMENT OF THE INTERIOR

5. LEASE DESIGNATION AND RERIAL NO. LC-029419(A)

	GEOLOGIO CONTENTE						
APPLICATION	FOR	PERMIT	TO	DRILL,	DEEPEN,	OR PLUG BACK	
SVA, OPPICE	L X			DEEPEN		PLUG BACK [	

6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME

b. TYPE OF WELL WELL X 2. NAME OF OPERATOR Getty Oil Company

Skelly Unit S. FARM OR LEASE NAME

3. ADDRESS OF OPERATOR

9. WELL NO. 157 E

17. NO. OF ACRES ASSIGNED --

TO THIS WELL 40

P. O. Box 730, Hobbs, New Mexico 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*)

933

10. FIELD AND POOL, OR WILDCAT Grayburg Jackson, Fren 11. SEC., T., R., M., OR BLK. 7-River

Unit Ltr. H, 2600 FNL and 1310 FEL At proposed prod. zone

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE.

22, 17S, 31E

5 miles southwest of Maljamar, New Mexico 15. DISTANCE FROM PROPOSED\*

12. COUNTY OR PARISH | 13. STATE Eddy. N.M.

LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drig. unit line, if any) 18. DISTANCE FROM PROPOSED LOCATION

16. NO. OF ACRES IN LEASE 4040 4761 19. PROPOSED DEPTH

20. ROTARY OR CABLE TOOLS Rotary

TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 21. ELEVATIONS (Show whether DF, RT, GR, etc.)

MULTIPLE

September 1984

22. APPROX. DATE WORK WILL START\*

3848.1 23.

ANT

DRODOSED	CASING	AND	CEMENTING	PROGRAM
PRUPUSED	CASING	AND	CEMMINITING	Incomm

3900

				17/1 / · · · · · · · · · · · · · · · · · ·
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
17-1/2	13-3/8	48#	500	1 520 CIRCULATE
12-1/4	8-5/8	28#	1900	1100 = =
7-7/8	5-1/2	15.5#	3900	750 25 722 1
///	3 -/ -			네스 최 점 등 보다는 한 교육을 고급한 수다.

- The subject well will be drilled from surface to 500 with fresh water 1. and gel additives to condition the hole for running casing. From 500' to 3900' (TD) a brine of sufficient weight and gel additivies will be used to control formation pressures and condition the hole for electric logs and running casing strings.
- The pump and plug method will be used to cement all strings of casing. 2. The 5-1/2" casing will have the top of the cement tied into the surface casing.

(This well will be downhole commingled in the Fren Seven Rivers and Grayburg Jackson Queen San Andres pools.)

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive .zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

W. B. Cade

Dist. Oper. Manager

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

APLA MOTERY

Subject to Like Approval by State

---

APPROVED BY

	25.	