

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
(Other instructions
page side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT..." for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Hondo Oil & Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 2208, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1780' FNL & 660" FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3805' GL

5. LEASE DESIGNATION AND SERIAL NO.
LC-029435-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
J. L. Keel "B" Federal

9. WELL NO.
37

10. FIELD AND POOL, OR WILDCAT
Grayburg Jackson

11. SEC., T., R. M., OR BLM. AND SURVEY OR AREA
Sec. 5-T17S-R31E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

RECEIVED

AUG 01 '88

O. C. O.
OFFICE

CSF

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE FLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well @ 4:00 a.m. 6/30/88. Drilled 12 1/4" hole to 380'. Ran 9 jts. of 8 5/8" 24# J-55 8rd casing and set @ 380'. Cemented w/500 sx. Class "C" w/2% CC. Circulated cement. WOC 8 1/2 hrs. Tested BOP to 500 psi for 30 min. - held okay. Drilled out w/7 7/8" bit 7/3/88.

JUL 28 11 45 AM '88
CARL AREATA

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED *Ron Rifan*

TITLE Engineer

DATE 7/21/88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUL 29 1988

*See Instructions on Reverse Side

SJS