

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

RECEIVED
NATION AND SERIAL NO.

LC-029426-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT ACREMENTS NAME

8. FARM OR LEASE NAME

H. E. West "A"

9. WELL NO.

15

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson SR-Q-6-1A

11. SEC. T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 3-T17S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other _____

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____

2. NAME OF OPERATOR

Hondo Oil & Gas Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 2208, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

660' FNL & 330' FEL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

11/14/88

15. DATE SPUDDED

11/22/88

16. DATE T.D. REACHED

12/3/88

17. DATE COMPL. (Ready to prod.)

1/6/89

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

3990' GR

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

4090'

21. PLUG, BACK T.D., MD & TVD

4037'

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

4090'

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

3479-3684', 3713-3926', 3943-4046' Grayburg San Andres

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

CNL-LD-NGT, DLL-MSFL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24#	685'	12 1/4"	450 sx. Class C w/2% CC	circ'd
5 1/2"	17#	4090'	7 7/8"	1000 sx. HLC + 300 sx. Class C w/8% CalSeal	circ'd

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	3977'	

31. PERFORATION RECORD (Interval, size and number)

3943-4046' 25 holes
3713-3926' 66 holes
3479-3684' 71 holes

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3943-4046'	6000 gal. 20% CRA acid
3713-3926'	6000 gal. 25% NEFE acid
3713-3926'	40,000 gal. 30# x-linked gel + 55,000# 20-40 sand

33.* PRODUCTION CONT.

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
1/13/89		Pumping 2" x 1 1/2" x 20' RWTC				Producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
1/17/89	24		→	115	60	30	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
		→					

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

Vented

Mike Rogers

35. LIST OF ATTACHMENTS

Deviation survey, logs

ACCEPTED FOR RECORD
SJS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Ron Brown

TITLE

Engineer

DATE

JAN 31 1989
1/19/89

*(See Instructions and Spaces for Additional Data on Reverse Side)

CARLSBAD, NEW MEXICO

Eddy Co., NM

38. GEOLOGIC MARKERS

NAME	MEAS. DEPTH	TOP	
		TRUE VERT. DEPTH	
Rustler	662'	(+3339)	
Salado	848'	(+3153)	
Tansill	1816'	(+2185)	
Yates	1972'	(+2029)	
Seven Rivers	2280'	(+1721)	
Queen	2894'	(+1107)	
Grayburg	3301'	(+700)	
Premier	3478'	(+523)	
San Andres	3612'	(+389)	
Lovington Sand	3728'	(+273)	
TD	4090'		

Hondo Oil & Gas Company
H. E. West "A" #15
Sec.3-T17S-R31E
Eddy Co., NM
Completion Report
Page -2-

32. 3479-3684' Acidized with 6000 gal. 15% NEFE acid
3479-3684' Frac'd with 80,000 gal. 30# x-linked gel +
160,000# 20-40 sand