Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

UNITE STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OIL CONS COMMISSION

b.awer DD

Artesia, NM 88210 **FORM APPROVED**

Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. **SUNDRY NOTICES AND REPORTS ON WELLS** Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC 029435-B Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Well ØÎOI Well ☐ Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** Keel "B" #52 9. API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 30-015-28098 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 1310' FSL & 60' FEL, Sec. 6-T17S-R31E Grayburg-Jackson 11. County or Parish, State **Eddy County, NM** CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice **Altering Casing** Conversion to Injection Other TD & set surface csg Dispose Water (Note: Report results of mu Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Reached TD of 3715' on 10/22/94. Ran 5-1/2" csg as follows: 5 1/2 float shoe @ 3715' 1- jt 5 1/2" 15.5" csg 1-5 1/2" float collar @ 3672' 87 its 5 1/2" 15.5# J-55 LT&C Csg Cmtd csg as follows: 775 sx 35/65 POZ/"C" + 6% D20+ 10% D44 + 1/4 lb/sk, D29 + 2% D46 Slurry weight = 12.7 ppg Slurry yield = 2.01 cft/sx 375 sk Class C + 5% D44 (BWOC) + 0.39% D59 + 1/4 lb/sk D29 Slurry weight = 14.8 ppg Slurry yield = 1.36 cft/sx Circulated 285 sx cmt to surface 535 14. I hereby certify that the foregoing is true and correct (L), (EW MEXICO KAREN ROSA ENGINEERING TECHNICIAN Date 1/2/95 (This space for Federal or State office use)