Form 3160-5 (June 1990)

4. I hereby certify that the foregoing is true and correct

## UNITED STATES DEPARTMEN JF THE INTERIOR

NM OIL CONS COMMISSION

BUREAU OF LAND MANAGEMENT		FORM APPROVED  Budget Bureau No. 1004-0135
SUNDRY NOTICES AND REPORTS ON WELLS		Expires March 31, 1993  5. Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		LC-029435-B
Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name
SUBMIT	IN TRIPLICATE	N/A
1. Type of Well		7. If Unit or CA, Agreement Designation
Type of Well   Gas   Other		N/A
2. Name of Operator DEVON ENERGY OPERATING CORPORA	TION	8. Well Name and No.
3. Address and Telephone No.		J. L. Keel "B" #89
		9. API Well No.
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527		30-015-28261
4. Location of Well (Footage. Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
1194' FNL & 100' FEL, Sec. 8-17S-31E		Grayburg Jackson Q, SR, GB, SA
		11. County or Parish, State
		Eddy County, NM
CHECK APPROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, RE	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	Change of Plans
Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair	Water Shut-Off
	Altering Casing	Conversion to Injection
	Other Spud, TD'd & set csg	Dispose Water (Note: Report results of multiple completion on Well
3 Describe Proposed or Completed Operations (Clearly state all pro-		Completion or Recompletion Report and Log form
locations and measured and true vertical depths for all markers	tinent details, and give pertinent dates, including estimated date of starting and and zones pertinent to this work.)*	ly proposed work. If well is directionally drilled give subsurface
Spud well on 8/11/95.		
	as follows: 13 jts 8 5/8", 24#, J-55 ST&C	
Cemented csg as	s follows: Lead w/300 sxs Pacesetter Lite "	C' + 2% CaCl + 1/4 Hydy Cello-
flake. Tailed in w/200 sxs Class "C" + 2% CaCl <sub>2</sub> .		
Circ'd 75 sxs cmt to surface.		OCT 1 3 1995
Reached TD of 4290' on 8/18/9	os ©	NL CON. DIV.
Ran 5 1/2" production csg as follows: 101 jts 5 1/2", 15.5#, J-55, 8 <sub>I</sub>		
floor solls	- 0 4245'	ord 11 11 11 11 11 11 11 11 11 11 11 11 11
	r @ 4245'.	
Cemented csg as	s follows: Lead w/1240 sxs PSL "C" + 4%	gel + 5% salt + 1/4 lb/sk Cello-flake
Tailed in v	w/300 sxs Class H + 10% gypsum + 1/4 lb/s	k cello-flake.
Circ'd 80 sxs to	surface.	

KAREN BYERS ENGINEERING TECHNICIAN Title Date 8/31/95 This space for Federal or State office use pproved by Title Date onditions of approval, if any:

itle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to y matter within its jurisdiction.