

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
811 S. 1st St. NE
Artesia, NM 88210-2834

FORM APPROVED
Bureau No. 1004-0135
Expires March 31, 1993

C/S P

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT --" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil
2. Name of Operator
3. Address and Telephone

AROC (Texas) Inc.
4200 E Skelly Drive, Suite 1000
Tulsa, OK 74135 918-491-1100

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 330' FEL, Unit A
Section 31-T17S-R30E

5. Lease Designation and Serial No.
LC-060529
6. If Indian, Allottee or Tribe Name
7. If Unit or CA, Agreement Designation
8. Well Name and No.
Beeson "F" Federal No. 29
9. Well API No.
30-015-31164
10. Field and Pool, or Exploratory Area
Loco Hills QN-GB-SA
11. County or Parish, State
Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☒ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this zone.)*

07/07/00 Spud well. Drill to 490'. RIH w/11 jts 8 5/8" 24# casing. Set @ 490' w/325 sx Class C, 2% Calcium Chloride.
WOC. Redimix to surface - approved by BLM.

07/13/00 TD @ 3400'.

07/14/00 RIH w/79 jts 5 1/2" 15.5# casing set @ 3400'. Cemented w/650sx Halliburton Lite w/5# salt, 1/4# FloCele,
425sx C w/3% CFR-3, 5# Gilsonite, 1# salt, 3% LAP. Circulated 117sx to pit.

07/18/00 Perforate 2769', 2801', 02', 03', 04', 07', 11', 60', 80', 2905', 25', 27', 28', 55', 56', 92', 3014', 15', 34', 90',
3111', 20', (Grayburg) 3212' (Vacuum), 70', 71', 72', 3303', 05', 07', 09', (Lovington) 30 holes.

07/19/00 Acidized 3212' - 3309' (8 holes) w/2000 gals 15% NEFE acid w/34 ball sealers.

07/20/00 Acidized 2769' to 3120' (22 holes-Grayburg formation) w/2000 gals 15% NEFE acid w/70 ball sealers.

07/25/00 Fraced perms 2769' to 3309' (30 holes- Grayburg & San Andres formations) @ the rate of 60 BPM @ 3000 psi.
Pumped a total of 800 sx 16/30 brady sand, 200 sx 12/20 brady sand in concentrations of 1# to 5# 16/30 & 4# 12/20.

14. I hereby certify that the foregoing is true and correct

Signed

Thallia Marshall
Thallia Marshall

Title

Date 07/31/00

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Approved By

Title

Date

Conditions of approval, if any:

ORIG SGD. DAVID R. GLASS

Aug 1 3 2000

Title 18 U. S. C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side