

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Yates Petr Corp.</i>		Lease <i>Midwest H H Com.</i>		Well # <i>1</i>	
Location of Well	Unit F <i>1980NW</i>	Section <i>21</i>	Township <i>18</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor <i>Moran</i>			Type of Equipment <i>Rotary to start approx 3-7-77</i>		

APPROVED CASING PROGRAM

\* *witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>17 1/2</i>	<i>13 3/8</i>	<i>48</i>		<i>250</i>	<i>250 cu</i>
* <i>12 1/4</i>	<i>8 5/8</i>	<i>24</i>		<i>1650</i>	<i>550 "</i>
<i>7 7/8</i>	<i>4 1/2 to 5 1/2</i>	<i>11.6 to 17</i>		<i>9800</i>	<i>250</i>

Casing Data:

Surface *41* joints of *8 5/8* inch *24* # Grade *API New J-55*  
(Approved) (Rejected)

Inspected by *Selam Mermin* date *3-14-77*

Cementing Program

Size of hole *12 1/4* Size of Casing *8 5/8* Sacks cement required *775*

Type of Shoe used *Culds* Float collar used *Insect Btm* *2* jts welded *Thread-Lock*

ID of hole *16.35 KB* Set *16.248* Feet of *8 5/8* Inch *24* # Grade *J-55*

New-used csg. @ *16.24 GL* with *200* sacks neat cement around shoe *Class C 2800*  
+ *515* sax *Homer Lite* additives *5# Gilsomite* *4# Floce* *2% CC*

Plug down @ *8:45* (AM) (PM) Date *3-14-77*

Cement circulated *1.0* No. of Sacks *None*

Cemented by *Halliburton* Witnessed by *Selam Mermin*

Temp. Survey ran @ *1:30* (AM) (PM) Date *3-15 77* top cement @ *240'*

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: *Water 300-25, 330-40, 400-20, 455-70, 570-300, 1050-1167*

*1185-97, 1230-1326*

*Ran 1" to 240' Cont 1163x Class C 4% CC PD 3:00 AM*