

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

170000 COPY
SUBMIT IN TRIPPLICATE*
(Other instructions reverse side)

Form approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.
NM 0440087

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

MAR 26 1979

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Yates Petroleum Corporation

J. C. C.
ARTESIA, OFFICE

3. ADDRESS OF OPERATOR
207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FSL & 2310' FWL of Section 7-18S-25E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "CX" Com

9. WELL NO.
13

10. FIELD AND POOL, OR WILDCAT
Undesignated

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA
Sec. 7-18S-25E
Unit L NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3621' GR

12. COUNTY OR PARISH
Eddy

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) Set Prod. Csq.

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8750 - Ran 236 joints of 4 1/2" 11.6# & 10.5# K-55 LT&C casing as follows: 70 joints 11.6# (2214'), 134 joints 10.5# (5528'), 32 joints 11.6# (1008') (Total 8750') set at 8750', 1-Guide shoe at 8750' and Diff-Fill Collar at 8710'. Cemented as follows: 250 gallons mud flush, 470 sacks Howco-Lite, 6/10% CFR-2, 5#/sack KCL 200 sacks Class H 6/10% CFR-2, 5#/sack KCL. PD 12:00 PM 3-10-79. Tested to 1500#. OK. WOC and ran Temperature Survey and found top of cment at 6020'; WLPBTD 8710'.

RECEIVED

MAR 21 1979

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Christine Johnson TITLE Geol. Secty DATE 3-20-79

(This space for Federal or State office use)

APPROVED BY Joe D. Lara TITLE ACTING DISTRICT ENGINEER DATE MAR 23 1979

CONDITIONS OF APPROVAL, IF ANY: