

DISTRIBUTION		
SANTA FE	/	
FILE	/	
U.S.G.S.		
LAND OFFICE		
OPERATOR	/	

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

FEB 14 1980

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Lewis MW	
9. Well No. 1 1	
10. Field and Pool, or Wildcat Und. Atoka-Yeso	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

ARTESIA, OFFICE

Name of Operator
Yates Petroleum Corporation ✓

Address of Operator
207 South 4th Street - Artesia, NM 88210

Location of Well
UNIT LETTER E 2310 FEET FROM THE North LINE AND 990 FEET FROM THE West LINE, SECTION 33 TOWNSHIP 18S RANGE 26E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3385' GR

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 9½" hole at 8:00 PM 2-4-80.

Ran 26 joints of 7" 20# J-55 ST&C (1116') of casing set at 1084'. 1-Guide shoe at 1084'. 1-insert float at 1041'. Cemented w/200 sacks 50-50 Poz, 2% D-20 Bentonite, 5# D-42 Kolite, k/4# D-29 Cellophane flakes, 2% CaCl. Tailed in w/150 sacks Class C 3% CaCl. PD 2:15 PM 2-6-80. Cement circulated 35 sacks to surface. WOC 18 hours, cut off and nipped up. Reduced hole to 6½", drilled plug and tested to 600#. OK - resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY Christine Tomlinson TITLE Geol. Secty. DATE 2-13-80

APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE FEB 15 1980

CONDITIONS OF APPROVAL, IF ANY: