

File ✓

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other Temp. Abandon

2. NAME OF OPERATOR

Penroc Oil Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Drawer 831, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FSL, 1980' FEL

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other) Re-Complete

5. LEASE
NM-0428657

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
RECEIVED

7. UNIT AGREEMENT NAME
OCT 9 1980

8. FARM OR LEASE NAME
Arco-Federal O. C. D.

9. WELL NO.
1 ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME
Winchester Atoka (Gas)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
33-19S-28E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.
30-015-21731

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3335 DF, 3336.3 KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
SEP 30 1980
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-15-80 to 9-25-80
Rigged up completion unit. Set cast iron plug at 9750', Bailer dumped 35' cement on plug. Perforated 4 1/2" casing at 9630'. Squeeze cemented w/100 sacks class H cement. Drilled out cement from 9254' to 9635'. Pressure tested 4 1/2" casing to 1500# for 30 min. Held OK.
Perforated 4 1/2" casing in Cisco-Canyon 9645-9658' (13') w/ten holes. Acidized w/3000 gals. NEFE 15% acid. Swabbed and tested zone. Negative results.
Well shut-in awaiting approval from partners to plug and abandon. Will discuss plugging program with you at that time.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED B. J. Dillinger TITLE President DATE 9-30-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
OCT 6 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO