

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other Instructions on re-
verse side)

Printed on approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0559774

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

CC Tank Unit ~~Field~~

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28-19S-24E
Unit F NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 1980' FWL of Sec. 28-19S-24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3731' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☒

(Other) Set Prod. Casing ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 8947'; WLPBTD 8180'. Ran 56 joints of 4½" 11.6# K-55 LT&C (1806'), 176 joints of 4½" 10.5# K-55 ST&C (568'), 23 joints of 4½" 11.6# K-55 LT&C (748') (255 joints 8232') set at 8214' KB w/1-Guide shoe, diff. fill float collar set at 8182' KB. Cemented w/250 gallons of mud flush and 175 sacks of Halli-Lite cement w/1/2% CFR-2 + 5# KCL and 100 sacks of Class "H" w/1/2% CFR-2 + 5# KCL, displaced w/20 bbls KCL water and 110 bbls fresh water. PD 11:30 PM 5-30-76. WOC and tested to 1500#. OK. Ran Temperature Survey and found top of cement at 6990'.

Ran 2-3/8" tubing and Tubing Conveyed Gun and perforated 8101-8107' w/24 .32" holes. Natural completion at approx. 2 MMCFPD.

RECEIVED

JUN 14 1976

U. S. G.
ARTESIA, OFFICE

RECEIVED

JUN 10 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE

Geol. Secty

DATE 6-10-76

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

APPROVED
JUN 10 1976
R. L. BEEKMAN
ACTING DISTRICT ENGINEER