

LAKEWOOD STATE NO. 1

1980' FSL & FWL Sec. 25, T19S, R27E

Eddy County, New Mexico

POSED

P&A

GL-3462
KB-3478

WELL SCHEMATIC	CASING	SIZE	WEIGHT	GRADE	THREAD	DEPTH
		13 3/8	48 #		ST&C	425'
	CASING	8 5/8	24 & 32 #	K-55	ST&C	3000'
	TUBING	4 1/2	16.6 & 13.5 #	N-80		11,150'
	TUBING					
DESCRIPTION OF EQUIPMENT						DEPTH
Surface plug (10 sx)						
13 3/8" casing, 450 sx Class C cmt. to surface						425'
Cement plug 475'-375' (40 sx)						
MUD LADEN FLUID						
Cement plug 3050'-2950' (40 sx)						
8 5/8" casing, 1200 sx Halliburton Lite cmt. to surface						3,000'
100' in & out cmt. plug @ 4 1/2" csg. stub						
T.O.C. @ 8660'						
10 sx cmt. plug on top of CIBP						
CIBP @ 10,100'						
Perfs: 10,175'-10,181' (Atoka)						
Top of cement plug - 10,490'						
CIBP @ 10,500' w/ 10' cmt. on top						
Perfs: 10,583'-10,750' (Upper Morrow)						
CIBP @ 10,775'						
Perfs: 10,791'-10,948' (Lower Morrow)						
4 1/2" casing, 725 sx Class H, (P&A 11,091')						11,150'
PREPARED BY						DATE
Stephen A. Rinegar						5-25-90