

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED  
JUL 31 1979  
C. C. C.  
ARTEZIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 648
7. Unit Agreement Name
8. Farm or Lease Name State "G" Comm.
9. Well No. 1
10. Field and Pool, or Wildcat Angell Ranch (Morrow)
12. County Eddy

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>
Name of Operator Southland Royalty Company ✓		
Address of Operator 1100 Wall Towers West Midland, Texas 79701		
Location of Well UNIT LETTER E, 1980 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 19S RANGE 27E NMPM.		

15. Elevation (Show whether DF, RT, GR, etc.)  
3462.6' GR

### 6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

### 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drill 11" hole to 2442'. Run Compensated Neutron-Formation Density w/Gamma Ray-Caliper and Dual Leterolog w/RXO.  
Ran 8 5/8" 24# K-55 ST&C casing set @ 2442'. Cement w/600 sx Lite Cement w/6# salt and 1/4" Flocel/sx plus 200 sx Class "C" cement w/2% Calcium Chloride and 6# salt/sx. Plug down @7:45 AM 7-26-79. Circ out 150 sx. WOC 18 hrs. Nipple w/double 10" Ser 900 BOP, 10" Ser 900 Hydril and Drlg. Head. Test BOP and csg to 1500 psi for 30 minutes, hold OK. Drill ahead 7 7/8" hole.

### 8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. Harvey Carr</u>	TITLE <u>District Engineer</u>	DATE <u>7-27-79</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>JUL 31 1979</u>
CONDITIONS OF APPROVAL, IF ANY:		