

## CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

FEB 14 1980

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG-1082

SUNDY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK ARTESIAN RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator McClellan Oil Corporation	8. Farm or Lease Name Tres Amigos
3. Address of Operator P. O. Drawer 730, Roswell, New Mexico 88201	9. Well No. Runyan
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 19-S RANGE 23-E NMPM.	10. Field and Pool, or Wildcat Undesignated Ranch Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3971.4 G. L.	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

\*2/07/80: Drilled to 1730'. Ran 1709.3' of new J-55, 24 lb. 8-5/8" csg.  
Cemented w/ 1700 sx of cement as follows:  
200 sx Class "C"-1/4 lb. Cello Seal  
500 sx Pacesetter Lite with 1/4 lb. Cello Seal - 10% salt  
200 sx " " " " " " " " - 2% CaCl - 16.81 lb.  
50 sx " " " " " " " " - 3% CaCl  
100 sx " " " " " " " "  
250 sx " " " " " " " "  
150 sx " " " " " " " "  
150 sx " " " " " " " "  
50 sx " " " " " " " "  
50 sx " " " " " " " " - 2% CaCl  
Circulated 20 sx of cement

\* See Attachment

Test Witnessed by O. C. D. Representative.

2/08/80: Finished pumping plugs down annulus of 8-5/8" csg. Total elapsed time 22-1/2 hours.  
Pressured up to 1000 PSI, held 30 minutes. No drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Paul J. McClure</u>	TITLE <u>Operator</u>	DATE <u>February 8, 1980</u>
APPROVED BY <u>W. A. Gussert</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>FEB 25 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		