

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0554472

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation. Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL GAS WELL OTHER

JUL 21 1980

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
Yates Petroleum Corporation ✓

O. C. D.

8. FARM OR LEASE NAME
Irish Hills-Yeso NM Federal

3. ADDRESS OF OPERATOR
207 South 4th Street - Artesia, NM 88210 ARTESIA, OFFICE

9. WELL NO.
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT
Penasco Draw SA Yeso (Assoc.)

990' FNL & 2310' FWL of Section 12-19S-24E

11. SEC., T., R., M., OR BLK. AND SURVEY OR RE-
Sec. 12-19S-24E
Unit C NMPM

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3617' GR

12. COUNTY OR PARISH 13. STATE
Eddy NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) Spud

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 15" hole at 3:00 AM 6-30-80.

TD 362' - Ran 9 joints of 10-3/4" 30# ST&C (362') of casing set at 360'.

1-Texas Pattern Guide Shoe at 360' and insert float at 320'. Cemented w/ 350 sacks of Class C 4% CaCl. PD 6:30 PM 6-30-80. Circulated 40 sacks of cement to the surface. WOC 12 hours, backed off, reduced hole to 9 1/2", drilled plug, tested to 600# OK and resumed drilling.

TD 909' - Ran 32 joints of 7" 20# ST&C (915') of casing set at 909'. 1-Tex. Pattern Guide shoe at 909' and insert float at 869'. Cemented w/250 sacks Class C neat, 450 sacks 65/35 Poz, 8# Kolite, 1/4# celloflakes, 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. Cement did not circ. PD 12:15 AM 7-2-80. WOC, ran Temperature Survey, found top of cement at 403'. Spotted 25 sx Class C 4% CaCl. PD 6:15 AM 7-2-80. WOC 2 hrs. Ran 1", tagged cmt at 320', sptd 25 sx Class C 4% CaCl. PD 8:20 AM 7-2-80. WOC 1 hr, ran 1", tag cmt at 315', sptd 100 sx Class C 4% CaCl. PD 9:20 AM 7-2-80. WOC 3 hrs, ran 1", tagged cmt at 315', sptd 150 sx Class C 4% CaCl. PD 12:10 PM 7-2-80. Circ. 5 sx of cmt to surface. WOC 18 hrs, NU, tstd to 1500# OK, reduced hole to 6 1/2", drilled plug, tested to 600# OK and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED Christie Ingham

TITLE Geol. Secty.

DATE 7-17-80

(This space for Federal or State office use)

APPROVED BY (Sigs. Sec.) PETER W. CHESTER

TITLE ACTING DISTRICT ENGINEER

DATE JUL 18 1980

CONDITIONS OF APPROVAL, IF ANY: