Submit 3 Copies to Appropriate District Office	State of New Me E. ,y, Minerals and Natural Re		Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210	OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088		WELL AP! NO. 30-015-27777 5. Indicate Type of Lease STATE FEE X
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	JAN 1 9 1994		6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well: OIL GAS WELL X WELL	OTHER .		Patriot AIZ Com
2. Name of Operator YATES PETROLEUM CORI	M CORPORATION		8. Well No. 4
3 Address of Operator		05) 748-1471	9. Pool name or Wildcat North Dagger Draw Upper Penn
105 South 4th St., Artesia, NM 88210 (505) 748-1471 North Dagger Draw Upper Penn 4. Well Location Unit Letter N : 810 Feet From The South Line and 1980 Feet From The West Line			
Section 20 Township 19S Range 25E NMFM Eddy County 10. Elevation (Show whether DF, RXB, RT, GR, etc.) 3540' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS CASING TEST AND CEMENT JOB X OTHER: 12. Describe Proposed or Completed Operations (Clearly state all peninent details, and give perinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spudded 26" hole 2:00 PM 1-8-94. Set 40' of 20" conductor pipe and cemented to surface. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 4:30 PM 1-10-94. Notified NMOCD, Artesia, NM, of spud. Resumed drilling 14-3/4" hole 4:30 PM 1-10-94. Ran 26 joints of 9-5/8" 36# J-55 casing set at 1158'. Guide shoe set 1158', insert float set 1111'. Cemented with 900 sx Halliburton Lite "C" w/10# Gilsonite, 1/2# Flocele + 3% CaC12 (yield 1.99, wt 12.4). Tailed in with 200 sx "C" + 2% CaC12 (yield 1.32, wt 14.8). PD 4:50 AM 1-13-94. Bumped plug to 900 psi, float held 0K. Circulated 129 sacks cement. WOC. Drilled out 12:01 AM 1-14-94. WOC 19 hours and 11 mins. NU and tested to 1000 psi for 15 mins. Reduced hole to 8-3/4" and resumed drilling.			
SIGNATURE (L CL + 2 Class	true and complete to the best of my knowledge a	ad beid. TITLE Production S	upervisor
(This space for State Use) $SUPI$	ERVISOR, DISTRIC'E IS	TITLE	JAN 2 5 1994

APPROVED BY ----

CONDITIONS OF APPROVAL, IF ANY: