

CLSF

# OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-28033

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name  
Hinkle ALD

8. Well No. 1

9. Pool name or Wildcat  
North Dagger Draw Upper Penn

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well  GAS Well  OTHER

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South Fourth Street - Artesia, NM 88210

4. Well Location  
Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line  
Section 28 Township 19S Range 25E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3483' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

<b>NOTICE OF INTENTION TO:</b>		<b>SUBSEQUENT REPORT OF:</b>	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: <u>Perforate &amp; acidize</u> <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-18-94 - Loaded tubing and released packer. TOOH. Rigged up wireline. TIH with 4" casing guns and perforated 7712-7729' w/14 .42" holes. TIH with 7" packer and RBP. Set RBP at 7760'. Tested to 1500 psi. Set packer at 7665'. Spot acid. Broke perforations with acid on spot. Acidized perforations 7712-7729' w/8000 gallons 20% NEFE gelled acid with scale and paraffin inhibitor. Swabbing.

11-19-94 - Released well to production department.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE 11-22-94

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505-748-1471

(This space for State Use)

APPROVED BY SUPERVISOR, DISTRICT II TITLE \_\_\_\_\_ DATE DEC 8 1994