

Santa Fe, New Mexico

AREA 640 ACRES
LOCATE WELL CORRECTLY

George Turner

Box 95, Artesia, New Mexico

WELL RECORD

30-015-02350

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). **SURMIT IN TRIPPLICATE.**

Turner Company or Operator 1 92334 15 Address 20
28 Lease Well No. in of Sec. T.
R. 4620 N. M. P. M. 3300 Field, Sec. 13 County.
Well is feet south of the North line and feet west of the East line of
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Neal Wills Address Carlsbad, N. Mex.
If Government land the owner is George Turner Address Box 95, Artesia, N. Mex.
The Lessee is August 8, 42 Address Oct. 14 42
Drilling commenced Mac T. Anderson 13 Drilling was completed Box 95, Artesia, N. Mex.
Name of drilling contractor Address
Elevation above sea level at top of casing feet.
The information given is to be kept confidential until 19

795 807 OIL SANDS OR ZONES

No. 1, from _____ to _____ No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet. _____

No. 2, from _____ to _____ feet. _____

No. 3, from _____ to _____ feet. _____

No. 4, from _____ to _____ feet. _____

CASING RECORD

[illegible]

MUDDING AND CEMENTING RECORD

NO. OF FE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	7"	712'	75	Haliburton	none	none

PLUGS AND ADAPTERS

ing plug—Material _____ Length _____ Depth Set _____
ters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

ZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
"	20'	Solidified	40 gals	9-16-42	790-810'	Total depth 900'

Results of shooting or chemical treatment Shot increased production from 12 bbls to 22 bbls.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Cable tools were used from 0 feet to 500 feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing 9-20- 1913
The production of the first 24 hours was 200 barrels of fluid of which 100 % was oil;
emulsion; _____ % water; and _____ % sediment. Gravity, Be 38
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

J.W. Reddell	Driller	Jess Kelley	Driller
C.S. Powell	Driller		Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 22 Artesia, New Mexico Sept. 1962
Place Date

day of Sept. 1942

Name Mac T. Anderson

Position Operator

Representing **George Turner**

Company or Operator _____
Address Box 95, Artesia, N. Mex.

Commission expires 9-11-83

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
	100	30	Water and sand
100	125	25	Heaving sand
125	200	75	Sand
200	250	50	Sand and sheets of mud
250	300	50	Sand, red clay and gyp
300	350	50	Red clay, gumbo and gyp shells
350	400	50	Red bed and gyp
400	432	32	Red rock, gyp
432	592	160	Salt. Top of salt 432
592	612	20	Lime
612	620	8	Broken lime and gyp
620	700	80	Lime
700	720	20	Hard, grey lime. Set 7*00 at 712', cemented with 50 sacks cement around shoe, and 25 sacks through braden-head.
720	755	35	Hard, brown lime
755	765	10	Medium brown lime
765	775	10	Broken lime
775	780	5	Blue shale
780	788	8	Lime, grey, broken
788	795	7	Blue shale and broken lime
795	807	12	Shale, broken lime and sand
807	816	9	Sandy lime, Show OIL 795-807
816	830	14	Broken sandy lime
830	875	45	Broken sandy lime and shale
875	885	10	Hard, grey lime
885	895	10	Broken lime and shale
895	900	5	Sandy shale
900	908	8	Hard, light grey lime.
		T.D.	