

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN () Llicate*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029008 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

OO Ada Nicholas

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Only

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T20S, R29E

12. COUNTY OR PARISH

Edgy

13. STATE

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Tidewater Oil Company

3. ADDRESS OF OPERATOR

Box 249, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

330 FNL and 330 FNL, Sec. 25, T20S, R29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3315

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We propose to plug and abandon the OO Ada Nicholas Well #1 in accordance with MDOCC Order R-25-A. This well is no longer economical to operate.

We intend to pull all casing strings at their lowest free point and lay a solid cement plug from TD to surface. In the event we are unable to pull casing opposite the salt section, we will run a cement bond log to determine cement coverage, then perforate and squeeze if necessary. Attached is a sketch showing all available down hole information.

RECEIVED

SEP 14 1965

G. C. C.
ARTESIAN SURVEY

RECEIVED
SEP 13 1965
U. S. GEOLOGICAL SURVEY
ARTESIAN SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED C. E. Wade

TITLE Area Supt.

DATE 9-10-65

(This space for Federal or State office use)

APPROVED BY
CONTRIBUTOR'S APPROVAL, ANY:

SEP 13 1965
RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEER

TITLE _____ DATE _____

NOTIFY USGS IN SUFFICIENT TIME TO

WITNESS plugging operation

*See Instructions on Reverse Side