

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. LC-060150	
2. NAME OF OPERATOR Pan American Petroleum Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR Box 68 Hobbs, NM 88240		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL X 1650' FWL Sec 10 (N, SE/4 SW/4)		8. FARM OR LEASE NAME HARGRAVE-FEDERAL	
14. PERMIT NO.		9. WELL NO. 4	
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		10. FIELD AND POOL, OR WILDCAT P.C.A. (YATES)	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 15-20-30 N1/4 PM	
		12. COUNTY OR PARISH EDDY	
		13. STATE N.M.	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	REPAIRING WELL ☐	☒
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	ALTERING CASING ☐	
SHOOT OR ACIDIZE ☐	ABANDON* ☐	ABANDONMENT* ☐	
REPAIR WELL ☐	CHANGE PLANS ☐		
(Other) ☐			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposal to P.A. submitted 5/4/65 and provisional approval by U.S.G.S on May 7, 1965. Provisional and hole conditions necessitated abandonment as follows:

6-27-65, Moved in, rigged up, tagged bottom at approx 1598'.

6-28-65, Circulated hole w/ brine water and spotted 50% cement plug, 1595-1089'.

6-29-65, Shot 5 1/2" casing at 950'. Unable to pull. Circulated cement w/ 170 lb. Cemented outside 7" casing and filled cellar w/ 30 lb. cement. Erected P.C.A. Marker. (Plug - 960' to surface)

All cement used was Incon Di Early, sulphate resistant, saturated with pond brine.

Pan American's representative, M.L. Claiborne. Operations witnessed and approved by: For PCA - Mr Paul Corbin.
For U.S.G.S: Mr R.C. Bair Jr.

18. I hereby certify that the foregoing is true and correct.

SIGNED V. L. BELL TITLE Area Supt DATE 9-21-65

(This space for Federal or State office use)

APPROVED
COMMISSIONS OF APPROVAL IF ANY:
DEC 1965
H. L. BELL
ACTING DISTRICT ENGINEER

TITLE _____ DATE _____

*See Instructions on Reverse Side