IN M. U. U. G. COPY Form 9-331 (May 1963) IJN!TED STATES NITED STATES SUBMIT IN TRICATE.

INT OF THE INTERIOR (Other instriction on re-Form approved. Budget Bureau No. 42-R1424. DEPART. 5. LEASE DESIGNATION AND SERIAL NO. GEOLOGICAL SURVEY LC-065373 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.) 7. UNIT AGREEMENT NAME WELL X GAS WELL Big Eddy 2. NAME OF OPERATOR OF LEASE NAME PERRY R. BASS S. GEOLOGICAL BOLL AND FOOL, OR WILDCAT G. H. Cobb 3. ADDRESS OF OPERATOR OX 1178, Monahans, Texas 79756

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

At surface 660' from the south line and 660' from the west line of Box 1178, Monahans, Texas 79756 Section 23, Township 20 South, Range 31 East, Eddy County, New Mexico. Sec. 23, T-20-S, R-31 12. COUNTY OR PARISH 13. STATE 14. PERMIT NO. R-31-E 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3515 Orig. DF. New Mexico 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF : TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF BEPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON\* SHOOTING OR ACIDIZING ABANDON MENT\* REPAIR WELL CHANGE PLANS (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) On 4-27-70, rigged up DA&b Well Service unit. Pulled rods and tubing; checked for fill with sand pump (7173 PBTD. 7135 top of fill). Ran a 9-5/8" RTTS packer on 2-7/8" ODEUE tubing; set the RTTS packer at 6948. On 4-30-70, treated down 2-7/8" ODEUE tubing, thru perforations in 9-5/8" OD casing 7003-7016 and 7022-7035 with 10,000 gal. "My-T-Frac" (Halliburton) as follows: (1.) 60 bbls. fresh water containing 2% potassium chloride, 50 lbs. Adomite Aqua per 1000 gal., and 1 gal. surfactant per 1000 gal., at 7.5 obls. per min. After pumping in the first 38 bbls., pressure rose to 300 psi, declined to 2600 psi. (2.) 60 bbls. "My-T-Frac" gel, no sand, 50 lbs. WAC-9 per 1000 gal., at 2600-2150-2400 psi at 8.6 bbls. per min. (3.) 40 bbls. "My-T-Frac" gel containing 1 1b. 20-40 mesh sand per gal. and 50 lbs. WAC-9/1000 gal. at 2750-2900-3000 psi, at 8 bbls. per min. (4.) 40 bbls. "My-T-Frac" gel containing 2 lbs. 10-20 mesh sand per gal. and 50 lbs. WAC-9 per 1000 gal. at 3000-3400-2800 psi, at 8 bbls. per min. (5.) 40 bbls. "My-T-Frac" gel containing 3 lbs. 10-20 mesh sand per gal. and 25 lbs. WAC-9/1000 gal. at 2800-3200 psi, at 8 bbls. per min. (6.) 40 bbls. "My-T-Frac" gel containing 3 lbs. 8-12 mesh sand per gal. and 25 lbs. WAC-9/1000 gal. at 2900-3150-3000-2900 psi., at 8 bbls. per min. (7.) 40 bbls. "My-T-Frac" gel containing 4 lbs. 8-12 mesh sand per gal. and 25 lbs. WAC-9/1000 gal. at 2900-2700 psi, at 6.6 bbls. per min. (8.) 10 bbls. "My-T-Frac" gel, no sand, at 2800-2900 psi, at 5 bbls. per min. (9). 35 bbls. fresh water containing 2% potassium chloride and 1 gal. surfactant per 1000 gal., at 2900-2150-2250 psi, at 4.4 bbls. per min. Job completed at 10:58 a.m. Immediate shut down pressure 1100 psi. 10 min. shut down pressure 1025 psi. 775 obls. load water to recover. Cleaned out 35' of fill; ran pumping equipment. Resumed pumping 5:00 p.m. 5-4-70. All load recovered 5-11-70. Pumped 36 bbls. water and no oil on 5-12-70. Testing. 18. I hereby certify that the foregoing is true and correct TITLE Asst. Div. Mgr. DATE <u>May 13, 1970</u> (This space for Federal or State office use) a <u>+</u> APPROVED BY DATE

CONDITIONS OF APPROVAL, IF ANY: ACCEPTED FOR RECORD PURPOSES ACTING District Engineer MAY 14 1970 Date

\*See Instructions on Reverse Side