31/2/

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Sa	nta	Fe	.الأ. و	ويظيه
Lesso No. LC	0.7	0	4 (2_9
Unit		<u> </u>		

AND REPORTS ON WELLS
SUBSEQUENT REPORT OF WATER SHUT-OFF
November 8 , 19 63 $\begin{bmatrix} M \\ S \end{bmatrix}$ line and 660 ft. from $\begin{bmatrix} K \\ W \end{bmatrix}$ line of sec. 11 25-E N.M.P.M. (Meridian)
• • • • • • • • • • • • • • • • • • • •
ILS OF WORK see, weights, and lengths of proposed casings; indicate mudding jobs, coment-
other important proposed work)
to 2,200', total depth, as a dry hole. ' to 1650', 750' to 650', 350' to 250', asing. Heavy mud laden fluid to be be welded on top of 13-3/8" OD Casing, ground, to be attached to plate, and all Conservation Commission rules and
NOV 10 1003 NOV 12 1003 RECEIN EFFICE RECEIVED
writing by the Geological Survey before operations may be commissioned.
4. 3. 15. 15. 15. 15. 15. 15. 15. 15. 15. 15