

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
Bright Federal M-028347

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Bright Federal9. WELL NO.
110. FIELD AND POOL, OR WILDCAT
Indian Basin - Morrow11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA
Sec. 21, 12N, E23E12. COUNTY OR PARISH
Eliz.13. STATE
N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER2. NAME OF OPERATOR
Sun Oil Company3. ADDRESS OF OPERATOR
P. O. BOX 2712, Ocala, FLA 326654. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**1650' from line and 1682' from line of Sec. 21, 1/4 of Sec. 21.**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3883 RT

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐**Progress Report**

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

**6-8-64 - DST #6 - 8890-8944 - 5/8" x 1/4" chokes, no wtr cushion, tool open 3 hours.
Very weak blow - 30 min. DIP 117. - 30 min. final DIP 250. Mud T. In - 4310,
Mud wt. out 4319. Rec. 30' mud - no gas, no wtr.****6-9-64 - DST #7 - 9086-9115' - 3/4" x 1/4" chokes, no wtr cushion, tool open 1 hour,
gas to surface in 3 min. at flow 115 mcf per day. 30 min. DIP 330, 1 hr. final
DIP 330. Mud wt. In 4390, out 4417. Rec. 120' drilling mud and 1300' salt water.**

RECEIVED

JUN 18 1964

O. C. G.
ARTESIA, OFFICERECEIVED
JUN 15 1964
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Stan Reedlund

TITLE

Foreman

DATE

6/24/64

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
JUN 17 1964
H. L. SLEMMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.