

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 1 PLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 04825

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Yates Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

32-208-29E

12. COUNTY OR PARISH 13. STATE

Eddy New Mexico

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR
J.M. HUBER CORPORATION

3. ADDRESS OF OPERATOR
922 Vaughn Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FSL & 660' FEL Section 32, T-20-S, R-29-E,
Eddy County, New Mexico

14. PERMIT NO.

Blanket

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3247.6 GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Cementing surface casg. ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 704'. Ran 13-3/8" casing as follows: Bottom 20 joints (623.88') 48#, H-40; next 2 joints (63.30') 54.5#, J-55; landing joint (28.90') 48#, H-40. Set at 704'. Cemented w/600' sx Class "C", 4% gel, 2% CaCl, 1/4# celloflake per sx; followed w/200' sx Class "C", 2% CaCl, 1/4# celloflake per sx. Plug down at 1:45 P.M. February 2, 1967. Cement circulated. W.O.C. 24 hours. Pressure tested to 500 PSI for 30 minutes, held OK. Started drilling under surface casing at 4:30 P.M. February 3, 1967.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Supt. DATE 2/7/1967

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
FEB 8 1967
R. L. BELKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
FEB 8 - 1967
U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.