

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1-
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG 1420

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator J.M. HUBER CORPORATION ✓	8. Farm or Lease Name Humble State
3. Address of Operator 922 Vaughn Building, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 23 TOWNSHIP 21-S RANGE 27-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3228.5 GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 17-1/2" hole to 700'. Ran 13-3/8" casing as follows: Bottom 21 joints (643.25') 48#, H-40; top 2 joints (60.51') 54.5#, J-55. Set at 700'. Cemented with 500 sx Class "C", 4% gel, 2% CaCl, 1/4# flocele per sx, followed with 200 sx Class "C" 2% CaCl, 1/4# flocele per sx. Cement circulated. WOC 24 hours. Pressure tested casing to 500 PSI for 30 minutes - held OK.

RECEIVED

FEB 1 1967

RECEIVED

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>Alfred H. M. [Signature]</u>	TITLE <u>District Production Supt.</u>	DATE <u>1/31/1967</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>Assistant District</u>	DATE <u>1/31/1967</u>
CONDITIONS OF APPROVAL, IF ANY:		