

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved,
Budget Bureau No. 42-R1424.
6. LEASE DESIGNATION AND SERIAL NO.

NM-0338754

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ WELL GAS ☒ WELL OTHER

RECEIVED

7. UNIT AGREEMENT NAME

Springs Unit Federal

8. FARM OR LEASE NAME

2. NAME OF OPERATOR

Gulf Oil Corporation

FEB 5 1975

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

9. WELL NO.

3

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surfaceB. C. C.
ARTESIA, OFFICE

10. FIELD AND POOL, OR WILDCAT

Springs Upper Penn

11. SEC., T., B., M., OR BLK. AND
SURVEY OR AREA

Sec 34, 20-S, 26-E

-1980' EN & EL Section 34, 20-S, 26-E

1980/5 660/W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3221' GL

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Plugged and Abandoned

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8140' TD, 8118' PB.

Released tubing from Guiberson Type A packer at 8020' and pulled tubing. Set CIBP at 8008'. Loaded hole with 177 barrels of abandonment mud. Capped BP with 5 sacks of cement. Cut and recovered 5-1/2" casing from 4051'. Spotted 12 sack cement plug from 5453' wot 5353', across 1st Bone Springs at 5020'. Spotted 20 sack cement plug from 4101' to 4001', across 5-1/2" casing stub at 4051'. Spotted 30 sack cement plug from 2748' to 2648', across 8-5/8" shoe at 2741'. Spotted 15 sack cement plug from 50' to surface. Installed dry hole marker. Will advise when location is ready for inspection.

RECEIVED

DEC 18 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Area Engineer

DATE December 17, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side