

COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

30-015-20138

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	L-185

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole	7. Unit Agreement Name Cawley Unit
2. Name of Operator Atlantic Richfield Company	8. Farm or Lease Name Cawley Unit
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1800</u> FEET FROM THE <u>North</u> LINE AND <u>1880</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>22-N</u> RANGE <u>21-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 435' DF	12. County Eddy

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 7610' T.D. without encountering commercial hydrocarbons. The well was plugged and abandoned by setting the following common cement plugs:

30 sx 7467-7567 (Cisco Canyon)
30 sx 7181-7285 (Cisco Canyon)
30 sx 6400-6500 (wolfcamp)
60 sx 4856-5056 (wolfcamp)
30 sx 3250-3350 (Bone Springs)
30 sx 1750-1850 (Across 8-5/8" casing shoe)
10 sx 16- 50 (In top of well)

9.0#/gal mud was used to spot all plugs. 13-3/8" and 8-5/8" casing strings were left intact. A dry hole marker was erected. We will notify your office by letter when this location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED O. D. Bretches TITLE Dist. Dirg. Supervisor DATE 6-17-68

APPROVED BY R. J. Stamm TITLE OIL AND GAS INSPECTOR DATE AUG 21 1968

CONDITIONS OF APPROVAL, IF ANY: