

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE
(Other instructions
reverse side)LICATE
OR re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 15002

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Lario-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

McMillan (Morrow)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17-20S-27E

12. COUNTY OR PARISH

Eddy

18. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

JAN 20 1978

O. C. C.
ANNEA, OFFICE1. OIL ☐ GAS ☒ OTHER ☐

2. NAME OF OPERATOR

Meadco Properties, Ltd.

3. ADDRESS OF OPERATOR

P. O. Box 2236, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface 1650' FNL & 2160' FEL, Sec. 17, T-20-S, R-27-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3633 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/12/74 TD 10,665' shale. DST #4 10,440-10,480'. 20" pre-flow. Weak Blow. 60"
Initial Shut-in - 139#, 30" flow period - 46#, 60" final shut-in - 116#.
Temp. 170°. Recovered 90' drilling mud.9/13/74 TD 10,665' shale. 35 sack plugs of Class H cement were set at the following
depths: 10,250-10,350'; 8,200-8,300'; 6,500-6,600'; 4,700-4,800'; 2,650-
2,750'.
10 sack plug set in surface. Rig released 12:00 p.m. 9/13/74.
No casing pulled.

We will advise as soon as the location is ready for final inspection.

RECEIVED

SEP 18 1974
U.S. GEOLOGICAL SURVEY
ATLANTA, GA 30303

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 9/17/74

(This space for Federal or State office use)

APPROVED BY

TITLE ACTING DISTRICT ENGINEER

DATE JAN 14 1978

CONDITIONS OF APPROVAL, IF ANY: