

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Cities Service Oil Co.		Lease Tracy C. Co.		Well # 1	
Location of Well	Unit H	Section 32	Township 21	Range 27	County Eddy
Drilling Contractor 1950 FNL 660 FEL			Type of Equipment Rotary		

* WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 7/8"	48#		400'	Circ
12 1/4"	9 5/8"	32.3, 36#		3000'	Circ
8 3/4"	5 1/2"	17, 20#		11650'	8500'

Casing Data:

~~Surface~~ ^{INTER} 68 joints of 9 5/8 inch 36# # Grade NEW - L 55 - BOTTLE 156
CMT. BEATED (Approved) (Rejected)

Inspected by Tom R. Long date 3-27-75

Cementing Program

Size of hole 12 1/4 Size of Casing 9 5/8 Sacks cement required 700

Type of Shoe used GLIDE Float collar used YES Btm 3 jts welded YES

TD of hole 3004 Set 3012 Feet of 9 5/8 Inch 36 # Grade K 55 NEW LONE STAR

New-used csg. @ 3004 with 200 sacks neat cement around shoe

+ 900 sax Howe LITE additives 5# GILS 1/4" AC CURE

Plug down @ 2:25 (AM) (PM) Date 3-28-75

Cement circulated YES No. of Sacks 100

Cemented by HALLIBURTON Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by Tom R. Long

Remarks: PTA 4-28-75 AS FOLLOWS

10 SX 11000 - 11100 IN PLACE @ 4:07 AM 4-28-75

40 SX 10000 - 10100 " " 5:01 AM 4-28-75

40 SX 9350 - 9450 " " 5:55 AM " "

40 SX 8675 - 8775 " " 6:40 AM " "

40 SX 7600 - 7700 " " 8:00 AM " "

10 SX 6250 - 6350 " " 8:40 PM " "

40 SX 5025 - 5125 " " 9:25 AM " "

40 SX 2950 - 3050 " " 10:20 AM " "

... 0 1/2" W/DY HOLE MARKER WELDED IN PLACE.