

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANITAFE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

JUN 29 1976

**O. C. C.
ARTEBIA, OFFICE**

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LC-12

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT..." (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -----
2. Name of Operator Morris R. Antweil	8. Farm or Lease Name Mesa Macho
3. Address of Operator Box 2010, Hobbs, NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER O , 560 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 24 TOWNSHIP 20-S RANGE 27-E NMPM.	10. Field and Pool, or Wildcat Undesignated Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3340' GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 8:30 AM 25 June, 1976. Drilled 17-1/2" hole to 577' with no fluid returns. Cemented 17 jts. 13-3/8" 48# casing @ 577' w/350 sx. Class C cement containing 1/2#/sx Flocele and 2% Ca Cl₂ and 200 sx. Class C cement containing 2% CaCl₂. Plug down 5:40 AM 26 June 76. Did not circulate. Tagged top of cement @ 85' w/1". Filled annulus to surface w/11-1/2 yds ready mix. WOC 18 hrs. Tested 13-3/8" casing w/800 psi 20 mins. - OK. Drilling ahead w/12-1/4" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *R M Williams* TITLE Agent DATE 28 June 1976

APPROVED BY *Selan Mesmer* TITLE OIL AND GAS INSPECTOR DATE JUN 29 1976

CONDITIONS OF APPROVAL, IF ANY: