

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
U.S.G.S.		
LAND OFFICE		
OPERATOR	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

RECEIVED BY
OCT 11 1983
O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.
K-6854

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEED OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Form or Lease Name Stonewall WM State
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 2
4. Location of Well UNIT LETTER P <u>450480</u> FEET FROM THE South LINE AND 990 FEET FROM East LINE, SECTION 30 TOWNSHIP 20S RANGE 28E NMPM.	10. Field and Pool, or Acreage Undes. Delaware
11. Elevation (Show whether DF, RT, GR, etc.) 3243' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING
OTHER

PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK
COMMENCE DRILLING OPS.
CASING TEST AND CEMENT JOB
OTHER Intermediate Casing

ALTERING CASING
PLUG AND ABANDONMENT

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Lost circulation 1752'. Pumped 75 bbl pill and regained 75% returns. Ran 59 jts 8-5/8" 24# J-55 casing set 2410'. 1-Texas Pattern notched guide shoe set 2410'. Insert float 2369'. Cemented w/450 sacks Class "C" 4% gel, .3% CF-1, 3#/sack Hyseal, 2% CaCl2. Tailed in w/450 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:00 AM 10-6-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hrs. Ran Temperature Survey and found top of cement at 365'. Ran 1". Tagged cement 365'. Spotted 150 sacks Class "C" 4% CaCl2. PD 6:30 PM 10-6-83. Cement circulated 10 sacks. WOC. Drilled out 5:00 AM 10-7-83. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 10-11-83

APPROVED BY _____ TITLE Original Signed By
Leslie A. Clements
Supervisor District II DATE OCT 13 1983

CONDITIONS OF APPROVAL, IF ANY: