

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Corp.</u>		Lease <u>stonewall EP st. #6</u>		Well # <u>6</u>	
Location of Well	Unit <u>EL</u>	Section <u>30</u>	Township <u>20</u>	Range <u>25</u>	County <u>COOY</u>
Drilling Contractor	<u>LARUE 2</u>		Type of Equipment <u>ROTARY</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2'</u>	<u>13 3/8"</u>	<u>48 #</u>	<u>NEW</u>	<u>550'</u>	<u>CIRC</u>
* <u>12 1/4"</u>	<u>8 5/8"</u>	<u>24-28 #</u>	<u>"</u>	<u>2400'</u>	<u>CIRC</u>
<u>7 1/8"</u>	<u>5 1/2"</u>	<u>17-20 #</u>	<u>"</u>	<u>TD</u>	<u>TIED BK. TO 8 3/8"</u>

Casing Data:

Surface 60 joints of 8 5/8 inch 24 # Grade J-55

yes (Approved) (Rejected)

Inspected by BW Weaver date 11-9-83

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 200

Type of Shoe used Tex-Ar Float collar used Insert Btm 3 jts welded yes

TD of hole 2410 Set 2412 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 2412 with 200 sacks neat cement around shoe

+ 850 C sax 5 Gilsonite 2% cc additives

Plug down @ 7:00 (~~AM~~) (PM) Date 11-10-83

Cement circulated yes No. of Sacks 35

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_