

RECEIVED BY

Form 9-331-4

MAR 14 1985

O. C. D.

ARTESIA, OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.

Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-4 for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Discovery Operating, Inc. ✓ 1-915-683-5205

3. ADDRESS OF OPERATOR

800 N. Marienfeld, Ste 100, Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650' FSL & 1650' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

13 3/8" csg. @ 310', cement circulated. 8 5/8" csg. @ 2550', cement circulated, 4 1/2" casing @ 8005', TOC approx. 7400', TD = 8010'. Cast Iron Bridge Plug @ 7996' with 10' cement on top. Perfs from 7938-7976'. Move in and rig up pulling unit. Trip out of hole with tubing and packer. Move in and rig up wireline. Set 4 1/2" Cast Iron Bridge Plug @ 7860'. Bail 35 sxs on Cast Iron Bridge Plug. Cut 4 1/2" casing @ 7266' and pull out of hole with same. Run in hole to 7300' and spot 30 sx plug from 7300' to 7200' using brine and gel. Pull up hole and spot 30 sx plug from 4000' to 3900'. Pull up hole and spot 30 sx plug from 2600' to 2500'. Pull up hole and spot 95 sx cement from 360' to surface. Weld on dry hole marker and clean location. Rig down, and move off location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

June 7, 1984

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY

Post ID-2
3-22-85
P1A