

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

8 1992

O. C. D.
ADVISORY SERVICE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit J, 1980' FSL & 1980' FEL, Sec. 11-T20S-R30E

5. Lease Designation and Serial No.
LC-070207-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Foundation ALO Fed Com #1

9. API Well No.

30-015-27079

10. Field and Pool, or Exploratory Area

Wildcat Morrow

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Surface Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 36" hole 12:20 PM 9-13-92. Set 40' of 30" conductor and redi-mix to surface. Notified BLM Answering Service, Carlsbad, NM of spud. Resumed drilling 26" hole 9-16-92. Lost circulation at 331'. Mixed and pumped LCM - no returns. Ran 10 joints 20" 94# J-55 ST&C casing set 414'. Guide shoe set 414', insert float set 372'. Cmt'd w/500 sx PSL "C" w/1½% CaCl2, 1/4#/sx Celloseal, .3% CF-14 (yield 1.80, wt 12.8). Tail in w/400 sx "C" w/1½% CaCl2 1/4#/sx Celloseal, .3% CF-14 (yield 1.32, wt 14.8). PD 4:30 PM 9-17-92. Cement did not circulate. WOC 4-1/2 hrs. Ran Temperature Survey and found TOC @ 320'. Ran 1". Cemented w/495 sx "C" + 3% CaCl2. Circulated cement to surface.* WOC. Drilled out 8:00 PM 9-18-92. WOC 27 hrs and 30 mins. Reduced hole to 17-1/2" and resumed drilling.

*PD 9:52 AM 9-18-92.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Production Supervisor

Date 9-22-92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side