

SPERRY-SUN DRILLING SERVICES
SURVEY DATA16-JUN-1994
10:38:28OXY
GOVAB

MEASURED DEPTH	ANGLE DEG	DIRECTION DEG	VERTICAL DEPTH	LATITUDE FEET	DEPARTURE FEET	VERTICAL SECTION	DOG LEG
5995.00	17.75	218.60	5945.81	291.77 S	328.52 W	438.25	1.88
6057.00	17.50	216.60	6004.90	306.64 S	339.97 W	456.39	1.06
6120.00	17.00	215.60	6065.06	321.73 S	350.98 W	474.31	0.92
6182.00	16.50	216.60	6124.43	336.17 S	361.51 W	491.45	0.93
6245.00	16.00	215.60	6184.92	350.41 S	371.89 W	508.36	0.91
6308.00	15.50	214.60	6245.55	364.40 S	381.73 W	524.68	0.90
6370.00	14.75	213.60	6305.40	377.79 S	390.80 W	540.03	1.28
6431.00	14.50	211.60	6364.43	390.77 S	399.10 W	554.51	0.92
6492.00	14.25	211.60	6423.52	403.66 S	407.03 W	568.66	0.41
6554.00	14.25	211.60	6483.61	416.66 S	415.03 W	582.92	0.00
6678.00	13.50	209.10	6603.99	442.31 S	430.07 W	610.46	0.77

THE DOGLEG SEVERITY IS IN DEGREES PER 100 FEET
THE VERTICAL SECTION WAS COMPUTED ALONG 232.50½

BASED UPON MINIMUM CURVATURE TYPE CALCULATIONS. THE BOTTOM HOLE
DISPLACEMENT IS 616.92 FEET IN THE DIRECTION OF 224.20½
COORDINATE VALUES ARE GIVEN RELATIVE TO THE PLATFORM REFERENCE POINT
VERTICAL SECTION IS GIVEN RELATIVE TO THE WELLHEAD LOCATION