

45F

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-9818

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

REMINGTON FEDERAL #3

9. API Well No.

30-015-27967

10. Field and Pool, or Exploratory Area

OLD MILLMAN Ranch Bore Spill

11. County or Parish, State

EDDY

SUBMIT IN TRIPLICATE

RECEIVED

AUG 22 '94

O.C.D.
ARTESIA, OFFICE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Chi OPERATING, INC

3. Address and Telephone No.

P.O. Box 1799, MIDLAND TX 79702 (915) 685-5001

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL + 1980' FWL SEC 3, T20S, R28E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☒ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1) Spud 17 1/2" hole WITH L+M Rig #1

2) Set 8 jts 13-3/8" 48# H-40 STC @ 350' w/ 3 cent. CMT w/ 400 sk Cl 'C' w/ 2% CaCl + 1/4 pps CALO. Circ'd 75 sk.

3) DRILL 12 1/4" hole to 3000'. SET 66 jts 8-5/8" 24# + 32# J-55 CSG w/ 20 cent. CMT w/ 1080 sk 'C' LITE + 10 pps SALT + 1/4 pps CALO FOLLOWED BY 250 sk 'C' + 2% CaCl + 1/4 pps CALO. DID NOT CIRC. WOC 6 hrs. Temp survey TOC 600'. TIT w/ 1" + TAG TOC @ 600'. CMT w/ 500 sk Cl 'C'. CIRC 15 sk.

4) DRILL 7-7/8" hole TO 6265'. CORE 6265-6385. DRILL 7-7/8" hole TO TD 6700'.

5) Ran 150 jts 4 1/2" 10.5# J-55 STC w/ 25 cent. CMT w/ 300 sk 'C' LITE + 700 sk 'C'. CALC TOC 154'.

6) Release Rig 4:00 PM MDT 7/26/94.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Date

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: