2:0015 mi

UNITED STATES

| NM | OIL | CONS | condisator | OVED |
|----|-----|------|-------------------|----------|
| n. | | ממ | Budget Bureau No. | 1004-013 |

| ine 1990) DEPARTMEN | STATES . JF THE INTERIOR .AND MANAGEMENT | NM OIL CONS COMMISSIONOVED Dr er DD Budget Bureau No. 1004-0135 Artesia NM 85210 March 31, 1993 5. Lease Designation and Secial No. |
|--|--|--|
| Do not use this form for proposals to dri | AND REPORTS ON WELLS II or to deepen or reentry to a different R PERMIT—" for such proposals | |
| SUBMIT | IN TRIPLICATE | 7. If Unit or CA, Agreement Designation |
| Type of Well X Gil | | 8. Well Name and No. Anemone ANE Federal #2 |
| Name of Operator YATES PETROLEUM CORPORATION | (505) 748-1471) | 9. API Well No. 30-015-27982 |
| Address and Telephone No. 105 South 4th St., Artesia, I Location of Well (Footage, Sec., T., R., M., or Survey D | राप्त 88210 escription) | 10. Field and Pool, or Exploratory Area Wildcat Canyon |
| 1090' FNL & 840' FWL of Section | n 9-T22S-R24E (Unit D, NWNW) | 11. County or Parish, State Eddy Co., NM |
| CHECK APPROPRIATE BOX(| s) TO INDICATE NATURE OF NOTIC | |
| TYPE OF SUBMISSION | | OF ACTION . |
| Nonce of Intent | Abandonment Recompletion | Change of Plans New Construction |
| X Subsequent Report | Plugging Back Casing Repair | Non-Routine Fracturing Water Shut-Off Conversion to Injection |
| Final Ahandonment Notice | Altering Casing Other Perforate & a | Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) |
| notes subsurface locations and measured and true vert 10-18-94 - Rigged up wireline. holes (1 SPF) as follows: 812 casing guns and rigged down with up wireline. TIH w/1-11/16" owith 1-11/16" GR. Rigged down Spotted 3-1/2 bbls 20% NEFE ac 8183'. Acidized perforations Communicated on tail end of fix RBP at 8230'. Reset RBP at 82 with 3000 gallons 20% NEFE ac Nippled down BOP. Nippled up 10-19-94 - Swabbing. 10-20-94 - Bled well down. Up | TIH with 4" casing guns and 27-8141', 8158-8163', 8170-8178 areline. TIH w/RBP, packer and GR. Correlated into place. Con wireline. Set RBP at 8230', and across perforations 812 82 8199-8216' w/1500 gallons 20% lush. Shut down. Unset packer 183' and reset packer at 8085', id and ball sealers. Knocked by | perforated 8127-8216' w/48 .40" B' and 8199-8216'. TOOH with 4" B 2-7/8" tubing to 8230'. Rigged prelated packer into place. TOOH Tested RBP to 1000 psi, OK. 216'. Moved and reset packer at NEFE acid and ball sealers. B 8183'. Dropped down and unserballs off. Reset packer at 8085'. BP at 8183'. TOOH with 2-7/8" |
| - And the state of | | |
| Signed Hustin Course Signed Hustin Horacoung is the and correct | | |
| (This space for Federal of State office use) Approved by | Title | Date |
| Conditions of approval, if any: | | JV |