Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

м	OTT	CONS	COMMIS	310
---	-----	------	--------	-----

Drawer DD FORM APPROVED
Artesia, Banes March 31, 1993
Expires: March 31, 1993

BUREAU OF L	NM 9818				
SUNDRY NOTICES A Do not use this form for proposals to dri Use "APPLICATION FOR	6. If Indian, Allottee or Tribe Name 7. If Unit or CA, Agreement Designation				
SUBMIT					
1. Type of Well Oil Gas Well Well Other		8. Well Name and No. 0086/7			
2. Name of Operator OXY USA Inc.	16696	9. API Well No. 30-015-28504			
2,00, 200, 00000	idland, TX 79710 915-685-5717	10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey De	RESE) Sec 3 Taos R28E	11. County or Parish, State Eddy NM			
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF SUBMISSION TYPE OF ACTION				
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Completion	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
,	AUG 08 Other side OIL CON DIST.	1995 1. DIV. = 6			
14. I hereby certify that the foregoing is true and correct Signed David	Stewart _{Title} Regulatory Analyst	Date 7/14/95			
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	Date			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ATTACHMENT 3160-5 OXY USA INC. GOVERNMENT S #7 SEC 3 T20S R28E EDDY COUNTY, NM

TD - 6680'

PBTD - 6636'

PERFS - 6306-6560'

MIRU PU 6/26/95, NU BOP, RIH & TAG @ 6636'. LOAD & TEST CSG TO 2000#, PUMP 750 GAL XYLENE + 750 GAL 15% NEFE HCL ACID, CIRC W/ 2% KCL FW. RIH W/ CBL, TOC @ 3060'. PERF BONE SPRINGS W/ 1SPF @ 6306, 22, 40, 55, 75, 6391, 6409, 28, 37, 55, 65, 77, 6494, 6503, 20, 42, 6560' TOTAL 18 HOLES. ACIDIZE W/ 2000 GAL 7-1/2% NEFE HCL ACID. FRAC W/ 80000 GAL SPECTRA FRAC G-3000 W/ 300000# 16/30 SAND, MAXP-1307#, ISIP-852#. SITP-200#, FLWD 150-BLW IN 4 HRS. RIH & TAG @ 6493', CLEAN OUT SAND TO 6634'. RIH TO 6634', NO FILL. RIH W/ BAKER LOK-SET, BAKER F NIP & 2-3/8" TBG, CIRC W/ PKR FLUID, SET PKR @ 6211', ND BOP, NUWH. TEST CSG TO 1000#, HELD OK. RIH W/ SWAB FOR 0-OIL 140-BLW, GOOD SHOW OF GAS IN 4 HRS. SITP-20#, SWAB & FLOW WELL FOR 100-BO 607-BLW IN 22 HRS, RDPU 7/7/95. HOOK UP TO TEST SEPR. & FLOW TEST WELL AS FOLLOWS:

TEST	FTP	OIL	WATER	<u>GAS</u>	CHOKE
24HRS	225	201	255	241	27/64
24HRS	270	333	358	277	27/64
24HRS	280	300	350	311	27/64
24HRS	285	293	261	270	27/64
24HRS	260	274	323	286	OPEN

NMOCD POTENTIAL TEST 7/13/95

24HRS 260 274 296 507 OPEN 40.5 - API GRAV OIL 1850 - GOR