


UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE



1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Matador Operating Company

3. Address and Telephone No.  
8340 Meadow Rd., #158, Dallas, TX 75231, 214-987-7144

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
660 FNL-1980 FWL  
Sec 4, T21S, R27E

5. Lease Designation and Serial No.  
NM 98124

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.  
Exxon Federal "4" #1

9. API Well No.  
30-015-30449

10. Field and Pool, or Exploratory Area  
Und Avalon Bone Spring East

11. County or Parish, State  
Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Run csg & cmt, TD  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log (nrm.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

(ORIG. SGD.) GARY GOURLEY

Drilled 11" hole to 2628'. Ran 63 jts 8-5/8" 24# J-55 ST&C csg. Set @ 2628'.

Cemented w/ 200 sx Thix w/ 5# sx Gilsonite, 1% CaCl<sub>2</sub>, 1/4#/sk/Celloflake + 450 sx H w/ 16% Gel, 2% salt, 5#sx gilsonite, 1/4# Celloflake. Tail in w/ 200 sx "C", 2% CaCl<sub>2</sub>. Did not circ any fluid. 600 psi final circ press. WOC & WO delivery f/ 1" top out. RIH beside csg w/ 90' 1" pipe. Tag @ 90'. Cmt w/ 130 sx "C" w/ 2% CaCl<sub>2</sub>. Cmt to surface. ND BOP's and test.

TD 7-7/8" hole @ 6,782' 11-8-98. Ran DIL-GR, CNL-LDL-GR-Cal logs. Ran 152 jts 5-1/2" 15.5# J-55 STC csg. Set @ 6782'. BJ cemented w/ scavenger slurry, 50 sx "C" @ 14.8 ppg followed by Lead of 850 sx Super C Modified (61# C, 15# Poz, 11# CSE) w/ 4 pps salt & 0.3% FL-52 mixed @ 13.0 ppg @ 1.69 CFS yld & 8.2 GPS water. Bump plug OK. Float held. ND BOP's, set slips. NU 11" 3M x 7-1/16" 3M tbg hd. Rig released 11-9-98.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Drilling Manager Date 11-13-98

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_  
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side

RECEIVED

NOV 18 98

BLM  
ROSWELL, NM