

Submit 3 Copies  
to Appropriate  
District Office

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico  
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

Form C-103  
Revised 1-1-89

WELL API NO.  
30-015-30899

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
K-4529

7. Lease Name or Unit Agreement Name  
South Avalon ASZ State Com

8. Well No.  
2

9. Pool name or Wildcat  
Burton Flat Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3162' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter L : 1650 Feet From The South Line and 660 Feet From The West Line  
Section 14 Township 21S Range 26E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2149'. Reached TD at 8:15 AM 2-14-2000. Ran 52 joints of 8-5/8" 24# J-55 (2154.54') of casing set at 2149'. 1-regular guide shoe set at 2148'. Float collar set at 2106'. Cemented with 50 sacks 65-35, 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.70, weight 11.0), 50 sacks 65-35, 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.30, weight 12.2) and 300 sacks Thixad "H", 10% A-10B, 1/4#/sack celloflake and 10#/sack gilsonite (yield 1.50, weight 14.6) and 550 sacks 65-35, 5#/sack salt, 1/4#/sack celloflake and 5#/sack gilsonite (yield 2.0, weight 12.5). Tailed in with 250 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 7:00 PM 2-14-2000. NOTE: Cement bridged 2 bbls before plug down. Went to 1500 psi and shut down with 2 bbls left in displacement to avoid breaking down formation losing cement job. WOC 6 hours and ran Temperature Survey and found top of cement at 1010'. Ran 1". Tagged cement at 894'. Spotted 35 sacks "C" with 4% CaCl2. PD 3:30 AM 2-15-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 891'. Spotted 50 sacks "C" with 4% CaCl2. Fluid at 255'. PD 5:30 AM 2-15-2000. WOC 1-1/2 hour. Ran 1". Tagged cement at 861'. Spotted 50 sacks "C" with

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 26, 2000  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR BGA

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUL 03 2000