## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Armerals and Natural Resources Department

| Form  | C-103     |
|-------|-----------|
| Revis | ed 1-1-00 |

|      |      | Ke | viseu |   |
|------|------|----|-------|---|
|      |      |    |       |   |
|      |      |    |       |   |
| <br> | <br> |    |       | _ |

| DISTRICT I<br>P.O. Box 1980, Hobbs, NM 83240  OIL CONSERVATION DIVISION P.O. Box 2088   | N WELL API NO. 30-015-31830   |  |  |
|---|---|--|--|
| DISTRICT II P.O. Diawer DD, Artesia, NM 88210  Santa Fe, New Mexico 87504-2088  | 5 Indicate Type of Lease  |  |  |
| DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 8741)   | STATE X  STATE X  FREE  6. State Oil & Gas Lease No.  V-4893  |  |  |
| SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)   |   |  |  |
| I. Type of Well:  OIL  WELL  OTHER  RECEIVES  | Whopper AZD State   |  |  |
| 2. Name of Operator YATES PETROLEUM CORPORATION  OCD - ARTESIA  | 8. Well No.   |  |  |
| 1 Address of Operator   | 9. Pool name or Wildcat   |  |  |
| 105 South 4th St., Artesia, NM 88210  4. Well Location  | Und. Revelation Morrow  |  |  |
| Unit Letter M: 990 Feet From The South Line and   | 990 Feet From The West Line   |  |  |
| Section 2 Township 22S Range 25E  10. Elevation (Show whether DF, RKB, RT, GR, etc.)  3578 GR   |   |  |  |
| 11. Check Appropriate Box to Indicate Nature of Notice  | ce, Report, or Other Data SUBSEQUENT REPORT OF:   |  |  |
| Notice of intention to:   |   |  |  |
| PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR   |   |  |  |
| MPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT   |   |  |  |
| PULL OR ALTER CASING CASING TEST AND CEMENT JOB   |   |  |  |
| OTHER: Prod   | uction casing & cement X  |  |  |
| 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date work) SEE RULE 1103.  |   |  |  |
| TD 11130'. Reached TD at 1:30 AM 8-27-2001. Ran 264 j 32 joints of 5-1/2" $17\#$ P-110 sandblasted (1324.47'); 1 blasted (531.50'); 37 joints of 5-1/2" $17\#$ N-80 varnish $17\#$ J-55 varnished (5961.65') and 41 joints of 5-1/2" 1 casing set at 11130'. Float shoe set at 11130'. Float marker set at 9806'. Cemented with 1050 sacks Super C 6/10% FL52 and $5\#$ /sack gilsonite (yield 1.57, weight 13 plug to 2410 $\#$ for 1 minute, OK. WOC. Released rig at | 3 joints of 5-1/2" 17# N-80 sand- led (1581.37'); 141 joints of 5-1/2"  17# L-80 varnished (11141.05') of  1 collar set at 11087'. Bottom  1 Modified (65-15-11), 6/10% FL25,  1 20. PD 2:30 AM 8-29-2001. Bumped |  |  |
| Waiting on completion unit.   |   |  |  |
|   |   |  |  |
| I hereby certify that the information above a true and complete to the best of my knowledge and belief.   | one Technician Oct 5 2001   |  |  |
| SIGNATURE   | ons Technician Oct. 5, 2001   |  |  |
| TYPEOR PRINT NAME RUSTY Klein   | TELEPHONE NO. 505/748-147   |  |  |
| (This space for State Use) / ORIGINAL SIGNED BY TIM W. GUM<br>DISTRICT II SUPERVISOR  | OCT 12 2001   |  |  |
| APTROVED BY TITLE   | DATE  |  |  |

CONDITIONS OF APPROVAL, IF ANY: