

Mightyl.txt

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	CLOSURE Direction Deg	Dogleg Severity Deg/100
7831.59	8.25	116.07	7661.14	-420.58	859.70	957.06	957.06	116.07	2.50
7861.59	7.50	116.07	7690.86	-422.38	863.39	961.17	961.17	116.07	2.50
7891.59	6.75	116.07	7720.62	-424.02	866.73	964.89	964.89	116.07	2.50
7921.59	6.00	116.07	7750.44	-425.48	869.72	968.22	968.22	116.07	2.50
7951.59	5.25	116.07	7780.29	-426.77	872.36	971.16	971.16	116.07	2.50
7981.59	4.50	116.07	7810.19	-427.90	874.65	973.71	973.71	116.07	2.50
8011.59	3.75	116.07	7840.11	-428.84	876.59	975.87	975.87	116.07	2.50
8041.59	3.00	116.07	7870.05	-429.62	878.18	977.64	977.64	116.07	2.50
8071.59	2.25	116.07	7900.02	-430.22	879.41	979.01	979.01	116.07	2.50
8101.59	1.50	116.07	7930.01	-430.65	880.29	979.99	979.99	116.07	2.50
8131.59	.75	116.07	7960.00	-430.91	880.82	980.58	980.58	116.07	2.50
8161.59	.00	116.07	7990.00	-431.00	881.00	980.78	980.78	116.07	2.50
Canyon Top--WELLBORE SHOULD BE RETURNED TO VERTICAL AT THIS POINT, WITH A BHL OF 650' N & E. DRILL REMAINDER OF WELL VERTICALLY									
8161.59	.00	116.07	7990.00	-431.00	881.00	980.78	980.78	116.07	2.60
8261.59	.00	116.07	8090.00	-431.00	881.00	980.78	980.78	116.07	.00
8361.59	.00	116.07	8190.00	-431.00	881.00	980.78	980.78	116.07	.00
8461.59	.00	116.07	8290.00	-431.00	881.00	980.78	980.78	116.07	.00
8561.59	.00	116.07	8390.00	-431.00	881.00	980.78	980.78	116.07	.00
8661.59	.00	116.07	8490.00	-431.00	881.00	980.78	980.78	116.07	.00
8761.59	.00	116.07	8590.00	-431.00	881.00	980.78	980.78	116.07	.00
8861.59	.00	116.07	8690.00	-431.00	881.00	980.78	980.78	116.07	.00
8961.59	.00	116.07	8790.00	-431.00	881.00	980.78	980.78	116.07	.00
9061.59	.00	116.07	8890.00	-431.00	881.00	980.78	980.78	116.07	.00
9161.59	.00	116.07	8990.00	-431.00	881.00	980.78	980.78	116.07	.00
9261.59	.00	116.07	9090.00	-431.00	881.00	980.78	980.78	116.07	.00
9361.59	.00	116.07	9190.00	-431.00	881.00	980.78	980.78	116.07	.00
9461.59	.00	116.07	9290.00	-431.00	881.00	980.78	980.78	116.07	.00
9561.59	.00	116.07	9390.00	-431.00	881.00	980.78	980.78	116.07	.00
9661.59	.00	116.07	9490.00	-431.00	881.00	980.78	980.78	116.07	.00
9761.59	.00	116.07	9590.00	-431.00	881.00	980.78	980.78	116.07	.00
9861.59	.00	116.07	9690.00	-431.00	881.00	980.78	980.78	116.07	.00
9961.59	.00	116.07	9790.00	-431.00	881.00	980.78	980.78	116.07	.00
10061.59	.00	116.07	9890.00	-431.00	881.00	980.78	980.78	116.07	.00
10161.59	.00	116.07	9990.00	-431.00	881.00	980.78	980.78	116.07	.00
10261.59	.00	116.07	10090.00	-431.00	881.00	980.78	980.78	116.07	.00
10361.59	.00	116.07	10190.00	-431.00	881.00	980.78	980.78	116.07	.00
10461.59	.00	116.07	10290.00	-431.00	881.00	980.78	980.78	116.07	.00
10561.59	.00	116.07	10390.00	-431.00	881.00	980.78	980.78	116.07	.00
10661.59	.00	116.07	10490.00	-431.00	881.00	980.78	980.78	116.07	.00
10671.59	.00	116.07	10500.00	-431.00	881.00	980.78	980.78	116.07	.00
TD WELL AT 10,500' TVD, 10,671' MD, RUN CASING OR P & A.									