

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE Distance FT	CLOSURE Direction Deg	Dogleg Severity Deg/100
6167.74	15.00	223.21	6143.87	-151.23	-142.08	207.50	207.50	223.21	.00
6267.74	15.00	223.21	6240.46	-170.10	-159.80	233.38	233.38	223.21	.00
6367.74	15.00	223.21	6337.06	-188.96	-177.52	259.27	259.27	223.21	.00
6467.74	15.00	223.21	6433.65	-207.82	-195.24	285.15	285.15	223.21	.00
6567.74	15.00	223.21	6530.24	-226.69	-212.96	311.03	311.03	223.21	.00
6667.74	15.00	223.21	6626.83	-245.55	-230.68	336.91	336.91	223.21	.00
6767.74	15.00	223.21	6723.43	-264.41	-248.41	362.79	362.79	223.21	.00
6867.74	15.00	223.21	6820.02	-283.28	-266.13	388.68	388.68	223.21	.00
6967.74	15.00	223.21	6916.61	-302.14	-283.85	414.56	414.56	223.21	.00
7067.74	15.00	223.21	7013.20	-321.00	-301.57	440.44	440.44	223.21	.00
7167.74	15.00	223.21	7109.80	-339.87	-319.29	466.32	466.32	223.21	.00
7267.74	15.00	223.21	7206.39	-358.73	-337.01	492.20	492.20	223.21	.00
7367.74	15.00	223.21	7302.98	-377.59	-354.73	518.08	518.08	223.21	.00
7428.66	15.00	223.21	7361.83	-389.08	-365.53	533.85	533.85	223.21	.00
END OF HOLD SECTION. BEGIN DROPPING ANGLE AT A RATE OF 2.5 DEG/100'									
7458.66	14.25	223.21	7390.86	-394.61	-370.72	541.43	541.43	223.21	2.50
7488.66	13.50	223.21	7419.98	-399.85	-375.64	548.62	548.62	223.21	2.50
7518.66	12.75	223.21	7449.20	-404.81	-380.31	555.43	555.43	223.21	2.50
7548.66	12.00	223.21	7478.50	-409.50	-384.71	561.86	561.86	223.21	2.50
7578.66	11.25	223.21	7507.89	-413.90	-388.85	567.91	567.91	223.21	2.50
7608.66	10.50	223.21	7537.35	-418.03	-392.72	573.57	573.57	223.21	2.50
7638.66	9.75	223.21	7566.88	-421.87	-396.33	578.84	578.84	223.21	2.50
7668.66	9.00	223.21	7596.48	-425.44	-399.68	583.73	583.73	223.21	2.50
7698.66	8.25	223.21	7626.14	-428.71	-402.76	588.23	588.23	223.21	2.50
7728.66	7.50	223.21	7655.86	-431.71	-405.58	592.34	592.34	223.21	2.50
7758.66	6.75	223.21	7685.62	-434.42	-408.12	596.06	596.06	223.21	2.50
7788.66	6.00	223.21	7715.44	-436.85	-410.40	599.39	599.39	223.21	2.50
7818.66	5.25	223.21	7745.29	-438.99	-412.42	602.33	602.33	223.21	2.50
7848.66	4.50	223.21	7775.19	-440.85	-414.16	604.88	604.88	223.21	2.50
7878.66	3.75	223.21	7805.11	-442.42	-415.64	607.04	607.04	223.21	2.50
7908.66	3.00	223.21	7835.05	-443.71	-416.85	608.80	608.80	223.21	2.50
7938.66	2.25	223.21	7865.02	-444.71	-417.79	610.18	610.18	223.21	2.50
7968.66	1.50	223.21	7895.01	-445.43	-418.46	611.16	611.16	223.21	2.50
7998.66	.75	223.21	7925.00	-445.86	-418.87	611.75	611.75	223.21	2.50
8028.66	.00	223.21	7955.00	-446.00	-419.00	611.95	611.95	223.21	2.50
Canyon Top, WELLBORE SHOULD BE RETURNED TO VERTICAL AT THIS POINT, AT A BHL OF 660' N & 1,980' E									
8028.66	.00	223.21	7955.00	-446.00	-419.00	611.95	611.95	223.21	2.76
8128.66	.00	223.21	8055.00	-446.00	-419.00	611.95	611.95	223.21	.00
8228.66	.00	223.21	8155.00	-446.00	-419.00	611.95	611.95	223.21	.00
8328.66	.00	223.21	8255.00	-446.00	-419.00	611.95	611.95	223.21	.00
8428.66	.00	223.21	8355.00	-446.00	-419.00	611.95	611.95	223.21	.00
8528.66	.00	223.21	8455.00	-446.00	-419.00	611.95	611.95	223.21	.00