

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 5 1976

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

O. C. C.

ARTESIA, OFFICE

RECEIVED

AUG 11 1976

O. C. C.  
ARTESIA, OFFICE

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Husky Oil Company of Delaware		8. Farm or Lease Name Forehand
3. Address of Operator 600 South Cherry St., Denver, CO 80222		9. Well No. #2
4. Location of Well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>West</u> LINE AND <u>1880</u> FEET FROM THE <u>South</u> LINE, SECTION <u>15</u> TOWNSHIP <u>23S</u> RANGE <u>27E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3127' Ground		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Intermediate Casing

7/12/76 Drilled to 1975'. Circulated 1 hr. Ran 48 jts. 8-5/8" K-55 8 rd. STC casing. Set at 1966' K.B. Cemented with 325 sacks of Halliburton Lite, 5# gilsonite, 4# celoflake. Tail in with 300 sacks cement, Class C, w/2% Cacl. Plug down at 10:30 p.m. Circulated to surface. W.O.C 16 hrs ~~7/12/76~~ 08/09/76

7/13/76 Nippled up BOP and pressure tested same to 800#. Tested O.K. Drilled cement plug and float from 1925' to 1965'. Washed to bottom. Tested casing to 1000#. Tested O.K. Began Drilling Plug @ 2:30 7/12/76 ~~7/12/76~~ 08/09/76

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Drilling Engineer DATE 8/2/76

APPROVED BY For Record Only TITLE SUPERVISOR, DISTRICT II DATE AUG 12 1976

CONDITIONS OF APPROVAL, IF ANY: