

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

MAY 11 1978

O. C. C.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT TO DRILL OR RE-ENTER FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator The Eastland Oil Company ✓	8. Form or Lease Name Harroun "A"
3. Address of Operator 704 Western United Life Building, Midland, TX 79701	9. Well No. 2
4. Location of Well UNIT LETTER A 330 FEET FROM THE North LINE AND 976 FEET FROM East THE LINE, SECTION 32 TOWNSHIP 22S RANGE 28E N.M.P.M.	10. Field and Pool, or Wildcat Undesignated Delaware
11. Elevation (Show whether DF, RT, CR, etc.) 3012' CR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Harroun "A" #2 was spudded at 12:00 noon April 30, 1978 using Cortez Drilling Co. cable tool rig. A 10" hole was drilled to 360' and 9 joints of 24#, J-55, 8 5/8" casing was set at 358'. The casing was cemented with 250 sacks Class C, 2% CaCl₂ with cement in place at 11:45 a.m., May 8, 1978. Approximately 75 sacks of excess cement was circulated out.

After allowing cement to set 20 hours, the casing was bailed dry. The cement and shoe were drilled at 1:00 p.m., May 9. The casing was bailed dry and again bailed after 30 minutes. There was no water entry.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED George D. Neal TITLE Superintendent DATE May 10, 1978

APPROVED BY W. A. Grossett TITLE SUPERVISOR, DISTRICT II DATE MAY 12 1978

CONDITIONS OF APPROVAL, IF ANY: